



PRODUCT REFERENCE: TONGUE S3 SRC

CODE : BC20023 – STYLE & JOB

SIZES : 35 to 48

DESCRIPTION : Low shoe

WEIGHT : 562 gr. half pair

PRODUCT ADVANTAGES

Classic and strong safety shoe with an excellent **quality/price** ratio

Steel Toe cap for a full protection

Stress Out System: tongue for extra comfort

SOLES CHARACTERISTICS

Assembling : Strobel

Comfort inner layer : **Soft PU 0,50** density

Pierce-resistance : **Classic steel midsole**

Sole : **PU/PU** anti-slip, antistatic

Outer sole density : **1,00**

WEARING CHARACTERISTICS

Last : **Natural Confort 11** Mondopoint

Toe cap : **Steel Toe** non perforated safety toe cap, weight **93 g**, 200 joules as per EN ISO 20345 norm

Resistance to shock in mm : 16,5 (Norm ≥ 14)

Resistance to compression in mm : 17,5 (Norm ≥ 14)

Footbed : **Flat-Fit**, removable anatomical footbed

UPPER CHARACTERISTICS

Water resistant black leather **2 mm**

Lining : **WING TEX** air tunnel textile lining material

Lacing : 4 galvanized D rings, **Polyester** laces (> 15000 frictions at 250 g as per DIN4843 Standard)

Tongue : stress-out patented®

Tongue label: product name, size, producer's name, manufacturing date (month/year), European standard reference, Style identification, protection class, CE marking

PROTECTION

Safety shoe

Norms : This product was tested according CE standard EN ISO 20345 : 2011 by an agreed institute

CE No 0161/17096/10

SLIP RESISTANCE

| SRC (SRA+SRB) | SRA TEST FLOOR CERAMICS LUBRIFICANT WATER +DETERGENT | FLAT HEEL CONTACT ANGLE 7° | EUROPEAN STANDARDS | U-POWER |
|---|---|-------------------------------------|-----------------------|---------|
| | | | ≥ 32 | 0,41 |
| SRB TEST FLOOR STEEL LUBRIFICANT GLYCERIN | FLAT HEEL CONTACT ANGLE 7° | ≥ 0,28 | 0,33 | |
| | | ≥ 0,18 | 0,18 | |
| | | ≥ 0,13 | 0,14 | |