



**PRODUCT REFERENCE: ARI S1P SRC**

**CODE : UF20046 – FLAT OUT**

**SIZES : 35 to 48**

**DESCRIPTION : Low shoe**

**WEIGHT : 508 g half pair**

## PRODUCT ADVANTAGES

Extra light aluminium with ergonomically designed sole pattern and tread offering unparalleled slip resistance

**Air Toe Aluminium** will let your feet breathe

**Stress Out System:** tongue for extra comfort

## SOLES CHARACTERISTICS

Assembling : Strobel

Comfort inner layer : **Soft PU 0,35** density

Pierce-resistance : **Save & Flex PLUS**

Sole : **PU/PU TR GRIP** antislip, antistatic, oil resistant

Outer sole density TR : **1,00**

## WEARING CHARACTERISTICS

Last : **Natural Confort 11** Mondopoint

Toe cap : **Air Toe Aluminium** perforated safety toe cap with breathable membrane, weight **54 g**, 200 joules as per EN ISO 20345 norm

Resistance to shock in mm : 15 (Norm  $\geq 14$ )

Resistance to compression in mm : 16 (Norm  $\geq 14$ )

Footbed : **Polysoft** anatomic insole made from soft polyurethane, with open pockets in the area of the foot support

## UPPER CHARACTERISTICS

Microfiber upper **2 mm**, ultra-light and breathable

Lining : **WING TEX** air tunnel textile lining material

Lacing : 4 perforated microfiber + 1 plastic eyelet, **Polyester** laces (> 15000 frictions at 250 g as per DIN4843 Standard)

Tongue : stress-out patented®

Tongue label: product name, size, producer's name, manufacturing date (month/year), European standard reference, Style identification, protection class, CE marking

## PROTECTION

Safety shoe

Norms : This product was tested according CE standard EN ISO 20345 : 2011 by an agreed institute

CE No 0161/22604/15

### SLIP RESISTANCE

		EUROPEAN STANDARDS		U-POWER
SRC (SRA+SRB)	SRA TEST FLOOR CERAMICS LUBRIFICANT WATER +DETERGENT	FLAT	$\geq 32$	<b>0,71</b>
		HEEL CONTACT ANGLE 7°	$\geq 0,28$	0,52
	SRB TEST FLOOR STEEL LUBRIFICANT GLYCERIN	FLAT	$\geq 0,18$	0,32
		HEEL CONTACT ANGLE 7°	$\geq 0,13$	0,23