

# SOFTANE™ Tradition

## JALASKA SAS J0266

**S3 CI SRC**  
**EN ISO 20345:2011**  
**36 to 48**

**Softane™**  
Tradition



- Full grain **AP 23** leather
- **Softane™** dual-density sole

- ❖ Natural-coloured boot with 2 leather side tabs for rapid pull-on
- ❖ Upper in water and oil resistant full grain **AP 23** leather, exclusive to :
  - ⊕ **10 to 15% thicker** (2,4 mm) than most leathers used for safety footwear
  - ⊕ **Resistance to penetration of water vapour three times higher** than the minimum fixed by european standard
- ❖ Flat binding at top of quarters
- ❖ Heel stiffener to reinforce the heel seat
- ❖ Full-size inlay, removable, anti-bacterial treated, anatomical and comprising heel shock absorber. High capacity to absorb and desorb perspiration.
- ❖ Forefoot lining, resistant to abrasion and perspiration acids
- ❖ Dual density **Softane™** sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability  
Heel shock absorption 29 Joule

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic/lubricant : water and detergent

On flat 0,58 (>0,32) – On the heel 0,54 (>0,28)

**SRB** Test ground steel/lubricant : glycerine

On flat 0,37 (>0,18) – On the heel: 0,14 (>0,13)

- ✓ Wraps round the foot for increased stability when walking
- ◆ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons
- ✓ Abrasion resistance : 80 mm<sup>3</sup>
- ✓ Puncture-resistant stainless steel midsole
- ✓ Perforated steel toe-cap (patented) – 200 J

Weight	Gross weight (42): 1740 g / Net weight (42): 1420 g												
Sizes	36	37	38	39	40	41	42	43	44	45	46	47	48
Packaging	5 pairs												
Dimensions (mm)	625x425x345												

Non contractual document  
Copyright JALLATTE  
Controlled distribution

04/06/2013

 **Jallatte®**  
www.jallatte.com